



BEAN•e•doo[®] 300RE Asphalt Remover

REMOVE ASPHALT QUICKLY & SAFELY

- Tackles tough asphalts, polymers, sealers, top coatings and more
- Low-odor, low-VOC formula made with 100% American-grown soybeans
- Easier clean up than traditional petroleum cleaners
- Can be pre-applied as a surface protectant



Coverage: Up to 200 square feet per gallon

See our full line of products

Visit: www.franmar.com or
Call: 800.538.5069





PRODUCT DATA



BEAN•e•doo® 300RE Asphalt Remover

Take off difficult, high-oil type asphalts with **BLUE BEAR® BEAN•e•doo® 300RE Asphalt Remover**. It effectively removes modified asphalts, polymers, top coating, coal tar and tac-coatings, keeping equipment and tools clean and free of build-up. Not only is **BEAN•e•doo** a great cleaner, it's a great protectant as well. Pre-applying to metal surfaces before using helps to keep asphalt from bonding tightly to the surface, making cleaning easier than ever! Made from 100% American-grown soybeans, **BEAN•e•doo** is simple to use on or off the job site and is safe for the environment.

Usage Tips:

- Pre-apply **BEAN•e•doo** to clean metal surfaces to help prevent asphalt from bonding.
- For large machinery or application areas, use a pump-up sprayer with chemical resistant seals.
- Build-ups of more than ½" thick may require multiple applications.

Coverage: Average coverage is 100-200 sq ft per gallon.

Application: Spray undiluted **BEAN•e•doo** directly on asphalt build-up. Let sit until build-up has softened. Thicker build-ups may require multiple applications or longer dwell times.

Clean Up: Spray clean with pressured hose or power washer.

Storage: Keep container closed when not in use.

Precautions: **BEAN•e•doo** is designed to break down asphalt based surfaces. Protect surfaces not intended for **BEAN•e•doo**.

Biodegradable: Meets or exceeds ASTM standards

Flash Point: Above 425°F (218.33°C)

pH Level: 6.65 pH of 1/10 wt/wt solution in soft water

CAUTION: May cause mild skin irritation. May cause eye irritation. May be harmful if swallowed. Keep out of reach of children.

Ingredients: Soy Ester, proprietary surfactant blend

VOC (Volatile Organic Compound) content:
2.3%, .06 lb/g, 20 g/l California and OTC Compliant

NON-EMERGENCY
Call: 800.538.5069
www.franmar.com
Bloomington, IL
61702

CHEMICAL EMERGENCY:
Spill, leak, fire, exposure or accident,
call CHEMTREC day or night.
USA and Canada: 800.424.9300
CCN717946 or +1 703.527.3887
(Collect calls accepted)



www.franmar.com
Rev. 12/19/22