



350RL

Asphalt Release for DOT Projects

Remove Asphalt Quickly & Safely

- Formulated to Meet DOT Regulations
- Concentrated Formula, 20:1 Dilution
- Improved and Increased Slips
- 100% Biodegradable



Find Out More About 350RL Asphalt Release for DOT Projects

Visit: www.franmar.com or
Call: 800.538.5069





PRODUCT DATA



350RL Asphalt Release for DOT Projects

350RL is specially formulated as 100% biodegradable and is non-petroleum based. **350RL** prevents bonding of hot asphalt mixtures when applied to truck beds and other metal surfaces such as spreader and tools.

Dilution:

20:1

Application:

Spray a light coat of **350RL** to metal surface using either a hand sprayer or a facility mechanical spray system to prevent sticking of asphalt hot mix.

Biodegradable:

Meets or exceeds ASTM standards

Warnings:

Causes mild skin irritation. Causes eye irritation. May be harmful if swallowed. Keep out of reach of children.

Flash Point:

Above 200°F (93.33°C)

pH Level:

7 - 9 pH of 1/10 wt/wt solution in soft water

VOC (Volatile Organic Compounds):

0.0%, 0.0 lb/g, 0 g/l
California and OTC Compliant

Ingredients:

Proprietary Non-Hazardous Surfactant and Additive

NON-EMERGENCY

Call: 800.538.5069

www.franmar.com

CHEMICAL EMERGENCY:

Spill, Leak, Fire, Exposure, or Accident

Call CHEMTREC Day or Night

USA and Canada: 800.242.9300

CCN717946 or +1 703.527.3887

(Collect Calls Accepted)



P.O. Box 5565
Bloomington IL 61702

Rev. 12/13/2016