



PRODUCT DATA



860LX Latex Form Release

Designed for the precast industry, **860LX** will not degrade latex forms. The highly concentrated formula has none of the hazards that come with using hydrochloric acid. Along with being safe to use and biodegradable, **860LX** has excellent wetability properties, will not stain, and produces a paintable surface.

Do not use or apply in a steady rain. Do not apply to forms still wet from rain or water used in cleanup. Use above 32°F (0°C).

Coverage:

Average coverage is 2,500 sq ft per gallon.

Mixing:

Add 1 part **860LX** to 30 parts clean water. Shake or mix the solution until consistent throughout. Once diluted, if left undisturbed for 1 month, solution may begin to separate. Shake or mix again until consistent throughout.

Application:

860LX can be applied by all conventional methods. Spray application is recommended. Remove puddles and allow to dry thoroughly. Proper application will result in fine detail with little to no dusting.

Clean Up:

Any spills or overspray can be cleaned with water.

Biodegradable: Meets or exceeds ASTM standards

Precautions:

Dispose of waste according to local regulations. Avoid eye contact. Gloves are recommended for sensitive skin.

Warnings:

Causes mild skin irritation. Causes eye irritation. May be harmful if swallowed. Keep out of reach of children.

Flash Point:

Above 200°F (93.33°C)

pH Level:

6.5 pH of 1/10 wt/wt solution in soft water

VOC (Volatile Organic Compounds):

0.1%, 0.01 lb/g, 1.2 g/l
California and OTC Compliant

Ingredients:

Trade Secret

NON-EMERGENCY

Call: 800.538.5069

www.franmar.com

CHEMICAL EMERGENCY:

Spill, Leak, Fire, Exposure, or Accident
Call CHEMTREC Day or Night

USA and Canada: 800.242.9300

CCN717946 or +1 703.527.3887

(Collect Calls Accepted)



PO Box 5565
Bloomington IL 61702

Rev. 1/28/2016