

MAKE LEAD NON-HAZARDOUS FOR REMOVAL & DISPOSAL!



QUICKLY STRIP LEAD-BASED PAINT

- One-of-a-Kind Product for Lead Remediation
- Renders Lead Paint Non-Hazardous for Safe Removal
- SAFE! No Methylene Chloride
- Made with 100% American-Grown Soybeans

COMES IN A READY-TO-USE KIT

- Mix Stabilizer Powder package thoroughly with Lead Based Paint Stripper.
- Apply a thick layer by brushing, pouring, or with a commercial sprayer.
- Use a scraper to check if the coating is softened down to the surface and remove when it is completely softened.
- Collect the converted lead coating(s) in a suitable container for disposal.

*Horizontal Coverage: 125 sq ft per gallon
Vertical Coverage: 75 sq ft per gallon*



See Our Full Line of Products

Visit: www.franmar.com or
Call: 800.538.5069





PRODUCT DATA



Lead Based Paint Stripper

(Formerly LEAD OUT™)

Franmar's proven paint removal technology combined with the patented Molecular Bonding System (MBS) takes the hazard out of removing and disposing of lead-based paint. **Lead Based Paint Stripper** reacts with the lead at the molecular level to convert the lead compounds to a non-hazardous waste that produces test results well below the EPA's lead safe limits. The result is a simple and affordable way to safely remove lead paint!

Coverage: Coverage per square foot varies depending on type and age of coating, number of layers and method of application.

Horizontal: Average coverage is 100 sq ft per gallon (max 200 sq. ft. per gallon)

Vertical: Average coverage is 50 sq ft per gallon

Test Area:

Due to variances in surfaces and conditions, always test in a small, inconspicuous area before using on complete project.

Usage:

Mixing: Open **Stabilizer Powder** package and mix thoroughly with **Lead Based Paint Stripper** Lead Paint Remover Gel. Once mixed, the product will only work for 24 hours to convert lead particles in the paint.

Application: Apply a thick layer by brushing, pouring, or with commercial sprayer. Applying too thin will cause **Lead Based Paint Stripper** to dry out before removal is complete. Use a scraper to check if the coating is softened down to the surface. If not, wait longer and recheck. When the coating is completely softened, remove with a scraper. Collect the converted lead coating(s) in a suitable container for disposal.

Clean Up: Use **BLUE BEAR General Purpose Cleaner & Degreaser** or water and a scrub brush, mop, or power washer to clean remaining thin residue. Remove excess coating(s) and **Lead Based Paint Stripper** before using a power washer for final cleaning. Allow surface to dry before further preparations.

Tips from the Pros:

- For large application areas, use a professional airless sprayer or a 4-stage HVLP sprayer.
- When used outdoors, cover with a 2mil or thicker plastic to help keep **Lead Based Paint Stripper** wet and working.
- Testing kits for lead content are generally available at hardware stores.
- For heavy lead content, contact Franmar for extra activation powder.

Biodegradable: Meets or exceeds ASTM standards

Precautions:

Some surfaces may darken with use of **Lead Based Paint Stripper**. Protect plants and vegetation with a plastic drop cloth. Always use care to prevent overspray from getting on surfaces other than the one being prepped or cleaned.

Warnings:

May cause skin irritation. May cause eye irritation. May cause respiratory irritation or may cause drowsiness and dizziness. May be harmful if swallowed. This product contains a chemical known to the state of California to cause birth defects or other reproductive harm. Keep out of reach of children.

Flash Point: Above 200°F (93.3°C)

pH Level: 8.3 pH of 1/10 wt/wt solution in soft water

VOC (Volatile Organic Compounds):

49%, 4.249 lb/g, 509 g/l, California and OTC Compliant

Ingredients:

N-Methyl Pyrrolidone, Dibasic Ester LVP, Soy Ester, Proprietary Thickening and Surfactant Blend. MBS ingredients are a trade secret.

NON-EMERGENCY

Call: 800.538.5069

www.franmar.com

CHEMICAL EMERGENCY:

Spill, Leak, Fire, Exposure, or Accident

Call CHEMTREC Day or Night

USA and Canada: 800.242.9300

CCN717946 or +1 703.527.3887

(Collect Calls Accepted)



PO Box 5565
Bloomington IL 61702

Rev. 6/23/2015