



# Your Safer PAINT STRIPPER

No Methylene Chloride.  
No NMP.



# BLUE BEAR PAINT STRIPPER With Safenol

-  Removes Paints, Urethanes, Enamels, Sealers, Some Epoxies, Lead Paint, + More
-  Removes Multiple Layers in ONE Application
-  SAFER! No NMP or Methylene Chloride
-  Non-Caustic and Biodegradable

## Paint Stripper with Safenol™

**Blue Bear Paint Stripper** is an effective stripper without using Methylene Chloride or NMP. Using BLUE BEAR's new Safenol™, this stripper effectively removes multiple layers of paint, varnish, enamel, urethane, other simple coatings, and lead based paint. **Paint Stripper** is a safe, low odor, biodegradable, non-caustic coating remover for any DIY project.

### Usage Tips from the Pros:

- Stripper can be reused if it maintains its gel consistency.
- When used outdoors, or for longer dwell times, cover with a 2 mil or thicker plastic sheeting over the work area to help keep stripper wet and working.

### Test Area:

Due to variances in surfaces and conditions, always test in a small, inconspicuous area before using on complete project.

### Application:

Apply a thick layer of **Paint Stripper** by pouring, brushing, squeegee, or commercial airless sprayer. Applying too thin will cause **Paint Stripper** to dry out before removal is complete. Use a scraper to check if the coating is softened down to the surface. If not, wait longer and recheck. When the coating is completely softened, remove with a scraper.

### Clean Up:

Use **BLUE BEAR General Purpose Degreaser** or water and a scrub brush, mop, or power washer to clean remaining thin residue. Remove excess coating(s) and **Paint Stripper** before using a power washer for final cleaning. Allow surface to dry before further preparations.

### Coverage:

Coverage per square foot varies depending on type and age of coating, number of layers, and method of application. Thickness of the stripper should exceed the thickness of coatings being removed.

**Horizontal:** Average coverage is 125 sq ft per gallon (max 200 sq ft per gallon)

**Vertical:** Average coverage is 75 sq ft per gallon

**Biodegradable:** Meets or exceeds ASTM standards

**Precautions:** Concrete surfaces may darken with use of **Paint Stripper**.

Protect plants and vegetation with a plastic drop cloth. Always use care to prevent overspray from getting on surfaces other than the one being prepped or cleaned.

**Warnings:** May cause eye irritation. Keep out of reach of children.

**Flash Point** None

**pH Level** 6.5

**VOC (Volatile Organic Compounds)** 3.1%, .25lb/g, 30g/l  
California and OTC Compliant

**Ingredients:** Dibasic ester, proprietary thickening, and surfactant blend

**Safe for Use On:** Concrete, masonry, wood, metal, and fiberglass \*Fiberglass must be attended. If left too long, Paint Stripper could degrade resin.

**Do Not Use On:** PVC, drywall, limestone, plastic, veneer, terrazzo tile, or rubber

 **WARNING:** Cancer and Reproductive Harm  
[www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**NON-EMERGENCY**  
Call: 800.538.5069  
[www.franmar.com](http://www.franmar.com)  
PO Box 5565  
Bloomington IL 61702

**CHEMICAL EMERGENCY:**  
Spill, Leak, Fire, Exposure, or Accident  
Call CHEMTREC Day or Night  
USA and Canada: 800.242.9300  
CCN717946 or +1 703.527.3887

Rev. 10/16/2018

franmar.com  
800.538.5069

